



Wireline Technologies SensorEngineering Feedthru Bulkhead Assembly

For harsh environment and high pressure applications, Wireline Technologies, with SensorEngineering of Germany, offers hermetically sealed glass feedthru bulkheads. Standard configurations include 4-contact, 10-contact, and 15-contact insert arrangements. For additional contact arrangements and custom design requirements, please contact us.



Technical Design Parameters for Glass Feedthru Bulkhead Assy:

- **Temperature:** 204 degrees C/400 degrees F
- **Pressure Rating:** 0 – 25,000 PSI (0 – 1724 BAR)
- **Shell Material:** 316L/17-4/Inconel
- **Current:** 2/3/5 AMPS Max per Contact
- **Insulation Resistance:** 500 MOhms min @ 500VDC
- **Leakage Rate:** 10E-9 mbar*1*x s-1

For sales contact:

WTI

19515 Oil Center Blvd.
Houston, Texas 77073
Tel: 281-209-9111
Fax: 281-209-9191

website

www.wirelinetech.com

e-mail

sales@wirelinetech.com

Specializing in Customized Gft Solutions

For design contact:

SensorEngineering
Robert Bosch Str. 12
D-78239 Rielasingen
Tel.: +49 7731 790764
Fax: +49 7731 790877
mail: info@sensorengineering.de